

# Amber Preprint

Amber Preprint is a high white, technically advanced, uncoated paper, developed for direct mail, invoices, letterheads and advertising material. The paper complies with the requirements of DIN 6723 and 6724-1 standards which means that the paper is guaranteed to work on equipment with optical character recognition (OCR). Amber Preprint works perfectly in digital presses and is also guaranteed to work in laser printers, even after offset litho printing. Thanks to its properties it can be used in high speed photocopiers and printers. Amber Preprint is available in both sheets and reels. Amber Preprint standard products are available as FSC<sup>TM</sup> and PEFC certified.

## AMBER PREPRINT, ECF - (APR 08)

Grammage (g/m <sup>2</sup> )	70 <sup>e</sup>	80	90	100	120	160
Opacity (%)	≥92	≥93	≥95	≥96	≥98	≥99
Thickness (µm)	91	104	117	130	156	208
Whiteness (CIE)						167
Roughness (Bendtsen, ml/min)	160	160	200	200	200	230
Screen recommended 133-150 lpi						
Permanent document, acid free ISO 9706						
Relative humidity at temp. 20-22 oC - 35%						
FSC, PEFC, ISO 14001, Paper Profile, EMAS						

Values are targets only and can be subject to changes over time without prior notice. You will find the latest valid technical specifications and information about our products at [www.arcticpaper.com](http://www.arcticpaper.com).

<sup>e</sup> Not standard production. Min. 30 tonnes and paper machine trim needed.

